Satin Low Finish Sealer

A PREMIUM WATERBASED ACRYLIC SEALER

COVERAGE:
1 gallon (3.8 Liters) covers approximately 300sq. ft. to 450 sq.ft.

PACKAGING:
Available in 1 gallon jugs, 5 gallon pails and 55 gallon drums.

STORAGE:
1. Store in a cool, dry location.
2. Store out of direct sunlight.
3. Protect pails and jugs from weather and other damage.
4. Store at a temperature between 40°F (4°C) and 90°F (32°C).

SHELF LIFE:
2 years

COLOR:
Milky, Dries Clear

Visit us online:
ClassicCoatingSystems.com

See Our Website Gallery to Get Inspired and View How-to Videos & SDS

DESCRIPTION

Classic Satin Low Acrylic Sealer is a clear single component sealer that is designed to be used over all of Classic's stains and on polymer-modified cement toppings, waterborne colorants, concrete, masonry, pavers, spanish tile, stucco, natural stone and brick. Be sure to properly prepare surfaces before applying. Classic Satin Low Acrylic Sealer is a waterborne acrylic with low voc , no fumes, low odors and high solids. May be used for interior or exterior applications in a wide range of climates. It is a excellent water repellent, provides high UV stability and will not yellow. It is formulated primarily as a clear seal for applications over concrete restoration projects and pool deck coatings. It is ideal for where a low maintenance, easily cleanable surface is desired. It is environmentally safe, has excellent adhesion, durability, low cost, easy installation and cleans up with soap and water. Available in 1 gal. jugs, 5 gal. pails and 55 gal. drums. Slippery when wet. Add Classic Gator Grip to combat slipperiness. **New concrete must cure for 28 days.**

ADVANTAGES

Resists water penetration
Waterborne: Low VOC <100g/l, no fumes and low odors
High UV stability
Excellent hot tire pick-up
Excellent adhesion and durability
Low cost, easy installation and low maintenance
Easy to clean with water.

LIMITATIONS

May reflect working cracks in substrate
Recommended application temperature should be between 55° F and 95° F
Must be installed over a clean dry surface
Not freeze thaw
Not for use under water
Surface must not contain moisture and efflorescence

TYPICAL USAGE

- Pool Decks
- Walkways
- Over stained concrete
- Restoration projects
- Architectural toppings
- Concrete floors
- Block walls
- Patios
- Masonry
- Spanish Tile
- Stucco
- Natural Stone

REVISED: April 2017

Classic Coating Systems • 255 Citation, Corona, CA 92880

© 2015 Classic Coatings Systems Inc. All rights reserved.

Satin Low Finish Sealer

A PREMIUM WATERBASED SEALER

PREPARATION

✓ **READ SDS BEFORE HANDLING & APPLICATION**
✓ Highly recommended to test a small inconspicuous area first.
✓ TURN OFF SPRINKLERS FOR TWO DAYS PRIOR TO AND AFTER.
✓ Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non-masonry surfaces.
✓ Caution: Surface is slippery when wet.
✓ New concrete must cure for 28 days before sealer is apply.

INSTALLATION

1. Prepare surface by carefully and thoroughly removing all traces of any foreign matter.
2. Apply 1st coat of Satin Low Sealer by a roller or sprayer.
Note: System thickness 1-2 wet mils. per coat. Do not allow to puddle. Puddles will result in a white haze.
3. Repeat step (2) for the 2nd coat.
4. A 3rd application may be required in high traffic areas. Cure Time at 77°F: Dry to touch in 30 minutes, re-coat after 1-2 hours, light foot traffic after 12 hours. Vehicle parking after 72 hours only and full cure in 7 days.

Note: Classic Satin Low Finish, when used with a small percentage of one of Classic's Pigment Concentrates can also provide a carrier for stain washing and faux finish techniques.

MAINTENANCE

For interior only: Clean with water and soap only. Do not use chemicals.

For exterior only: Clean with water. Improper maintenance will result in wearing out your surface. If this occurs, use Classic Stripper to remove sealers and stains in order to re apply desired stain and sealer. Note that Classic Stripper will remove any coats of sealers and stains on your surface.

PHYSICAL CHARACTERISTICS & TECHNICAL DATA

- Coverage per liquid gallon 300-450 sq ft per gallon
- Abrasion - Excellent
- VOC 62 g/l
- Degree of Gloss – Satin Low Finish
- Solids content by weight: 29.40%
- Solids content by volume: 26.40 %

It is HIGHLY recommended that on-site samples and mock-ups be made by the applicator. Representative test sections must be produced for the owner's approval in writing and to ensure that applicators are familiar with the product and installation procedures.

Disclaimer: The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind, express or implied is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers and users of this product must comply with all applicable health and safety laws, regulations and orders.

PRODUCT AVAILABILITY & TECHNICAL ASSISTANCE

Technical assistance and information is available by calling
(714) 720-6954
www.classiccoatingssystems.com

HANDLING PRECAUTIONS:
Use only with adequate ventilation. An appropriate cartridge type respirator must be used during application in confined areas. Avoid contact with skin. Protective gloves, eyewear and clothing are recommended.

PROP 65 WARNING:
Classic Coatings, as a blender of processed material in the State of California, is required by Proposition 65 to warn that one or more of the components contained in the product contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California (Proposition 65) requires this warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacturing, distribution and intended use. User is solely responsible for the legal disposal of this container and/or its contents.

WARRANTY:
Classic Coating products are warranted for one year after date of purchase. Please refer to the Limited Material warranty for additional clarification. NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY. We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET & FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.

© 2015 Classic Coatings Systems Inc. All rights reserved.
REVISED: April 2017