

# **SAFETY DATA SHEET**

Issue Date 3-July-2015 Revision Date 4-Nov-2024

### 1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PRO-SEAL 2000 WET-LOOK SEALER \*Exterior Use Only

PRODUCT CODE: CL401

MANUFACTURER
CLASSIC COATINGS SYSTEMS
255 CITATION CIR.
CORONA, CA 92878

COMPANY PHONE (951) 279-2600

24 HR. EMERGENCY TELEPHONE NUMBER Emergency Response Service: (800) 535-5053

### 2. HAZARDS IDENTIFICATION

**CLASSIFICATION** Flammable Liquid (category 3)

Serious Eye Irritation (category 2A)

**GHS Classification** Specific Target Organ Toxicity, Single Exposure:

Narcotic Effects (Category 3)

**US DOT Symbols:** 



EU and GHS Symbols:









Signal Word: Danger

Hazard Statements H225: Highly flammable liquid and vapor

H319: Causes serious eye irritation

H336: May cause drowsiness or dizziness

H315: Causes skin irritation

H317: May cause an allergic reaction H335: May cause respiratory irritation

H411: Toxic to aquatic life with long lasting effects

Precautionary Statements: P210: Keep away from heat, sparks, open flame, hot surfaces. No

Smoking

P240: Ground/bond container and receiving equipment

P241: Use explosion proof electrical/ventilating/lighting equipment

P242: Use only non-sparking tools

P243: Take precautionary measure's against static discharge P261: Avoid breathing dust/fumes/gas/mist/vapors/spray

P264: Wash hands thoroughly after handling

P271: Use only outdoors or in a well ventilated area

P280: Wear protecting gloves/protecting clothing/eye protection/face protection

P301+P330+P331+P313: If swallowed: Rinse mouth. Do not induce vomiting. Get medical attention.

P303+P361+P353: If on skin or hair: Remove all contaminated clothing. Rinse skin with water/shower.

P304+P340: If inhaled: Remove victim to fresh air and keep at rest in a postion comfortable for breathing.

P305+P351+P338: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do, Continue rinsing.

P312: Call a poison center or doctor/physician if you feel unwell.P337+P313: If eye irritation persists: Get medical attention/advice.

P370+P378: In case of fire: Use dry sand, dry chemical, or alcohol resistant foam for extinction.

P403+P233+P235+P405: Store in a wall ventilated place. Keep

container tightly closed. Keep cool. Store locked up. P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

### **EMERGENCY OVERVIEW**

**PHYSICAL APPEARANCE:** FLUID COLORED LIQUID WITH SOLVENT ODOR **IMMEDIATE CONCERNS:** Warning. Flammable liquid and vapor.

#### **POTENTIAL HEALTH EFFECTS**

**EYES:** EYES: EXPOSURE TO LIQUID OR VAPORS MAY CAUSE SEVERE EYE IRRITATION. SYMPTOMS MAY INCLUDE BURNING, TEARING, REDNESS, SWELLING, AND EYE DAMAGE.

**SKIN:** May cause skin irritation and sensitization.

**SKIN ABSORPTION:** PROLONGED OR REPEATED EXPOSURE MAY RESULT IN SKIN ABSORPTION OF TOXIC AMOUNT S OF MATERIAL.

**INGESTION:** SWALLOWING MATERIAL CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

**INHALATION:** EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION. CENTRAL NERVOUS SYTEM EFFECTS INCLUDE DIZZINESS,

WEAKNESS, FATIGUE, NAUSEA, HEADACHE AND POSSIBLE UNCONSCIOUSNESS AND EVEN DEATH.

**CHRONIC:** ASTHMA, BRONCHITIS, EMPHYSEMA, HYPERREACTIVITY, SKIN ALLERGIES, ECZEMA.

**CARCINOGENICITY:** None Known **MUTAGENICITY:** No known effects.

### REPRODUCTIVE TOXITY

**REPRODUCTIVE EFFECTS:** No known effects. **TERATOGENIC EFFECTS:** No known effects.

**IRRITANCY:** NO KNOWN ACUTE OR CHRONIC HEALTH HAZARDS.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous	WT%	CAS No.	EINECS No.	Hazard Classification
Ingredients				
Aromatic	< 10%	64742-95-6	265-199-0	Flam. Liq. 3; Skin Irrit. 2; Carc. 1B, Muta. 1B; STOT
Hydrocarbon				SE 3; ASP. Tox. 1, Aquatic Chronic 2
p-Chloro-a,a,a-	< 60%	98-56-6	202-681-1	Flam Liq Cat 3, STOT SE CAT 3 (Resp Irrit and CNS), Aquatic
triflourotoluene				Chronic Cat 2
Diisodecyl Phthalate	< 2%	68515-49-1	247-977-1	Aquatic Acute 1, Aquatic Chronic 1
Acetone	< 20%	67-64-1	200-662-2	Flam Liq Cat 2, Eye Irrit Cat 2A, STOT SE CAT 3 (Resp Irrit
				and CNS)

Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).

### 4. FIRST AID MEASURES

**EYES:** Flush with water for 15 minutes. See a physician.

**SKIN:** Wash skin with soap and water. See a physician if irritation persists.

**INGESTION:** INGESTION: DO NOT INDUCE VOMITING. KEEP PERSON WARM, QUIET, AND GET MEDICAL ATTENTION (911) IMMEDIATELY. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

**INHALATION:** INHALATION: REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

#### 5. FIRE FIGHTING MEASURES

FLASH POINT AND METHOD: 5.56 °C (42.01 °F) Closed cup

**FLAMMABLE LIMITS:** 1.0 TO 13.39

**AUTOIGNITION TEMPERATURE:** This product will not autoignite.

FLAMMABLE CLASS: Flammable liquid category 3

**GENERAL HAZARD:** Danger. Highly flammable liquid and vapor.

**EXTINGUISHING MEDIA:** Use foam, carbon dioxide or chemical fire fighting apparatus.

**FIRE FIGHTING PROCEDURES:** The use of self-contained breathing apparatus is recommended for fire fighters. Water spray may be used for cooling containers to prevent possible pressure build-up and autoignition or explosion when exposed to extreme heat. Avoid spreading burning liquid when using water for cooling containers.

**FIRE EXPLOSION:** CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT OR FLAME DUE TO PRESSURE BUILDUP. COOL CONTAINERS WITH WATER SPRAY. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. DO NOT USE WELDING EQUIPMENT OR CUTTING TORCH ON OR NEAR CONTAINER BECAUSE PRODUCT MAY IGNITE EXPLOSIVELY. THE SAME CAUTIONS APPLY TO EMPTY CONTAINER

#### 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** DIKE AND CONTAIN SPILLED MATERIAL. ELIMINATE IGNITION SOURCES SUCH AS FLAMES, PILOT LIGHTS, SPARKS AND FLARES. SCOOP UP MATERIAL AND PUT INTO SUITABLE CONTAINER.

LARGE SPILL: OBEY ALL LOCAL, STATE AND FEDERAL REGULATIONS.

#### **ENVIRONMENTAL PRECAUTIONS**

WATER SPILL: OBEY ALL LOCAL, STATE AND FEDERAL REGULATIONS.

LAND SPILL: OBEY ALL LOCAL, STATE AND FEDERAL REGULATIONS.

### 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** AVOID EXCESSIVE HEAT OR FLAME. DO NOT WELD ON OR NEAR CONTAINER.

KEEP CONTAINERS CLOSED WHEN NOT IN USE.

FOR INDUSTRIAL USE ONLY. KEEP OUT REACH FROM CHILDREN.

WASH HANDS BEFORE EATING.

### 8. EXPOSURE CONTROLS\PERSONAL PROTECTION

### **OSHA TABLE COMMENTS:**

NL = Not Listed

### **EXPOSURE LIMITS:**

Ingredients	CAS No.	OSHA PEL	NIOSH PEL
Aromatic Hydrocarbon	64742-95-6	2000 mg/m <sup>3</sup>	350 mg/m <sup>3</sup>
p-Chloro-a,a,a-triflourotoluene	98-56-6	100 mg/m <sup>3</sup>	100 mg/m <sup>3</sup>
Acetone	67-64-1	1000ppm 2400 mg/m <sup>3</sup>	250ppm 590 mg/m <sup>3</sup>
Diisodecyl Phthalate	68515-49-1	Not Listed	Not Listed

**ENGINEERING CONTROLS:** LOCAL EXHAUST RECOMMENDED.

MECHANICAL EXHAUST RECOMMENDED.

# PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: SAFETY GLASSES OR CHEMICAL SPLASH GOGGLES RECOMMENDED.

**SKIN:** IMPERMEABLE RUBBER GLOVES RECOMMENDED.

**RESPIRATORY:** USE NIOSH APPROVED ORGANIC VAPOR RESPIRATOR WHEN PERMISSIBLE

EXPOSURE LIMIT IS EXCEEDED.

WORK HYGIENIC PRACTICES: AVOID EXCESSIVE HEAT OR FLAME. DO NOT WELD ON OR

NEAR CONTAINER.

KEEP CONTAINERS CLOSED WHEN NOT IN USE.

FOR INDUSTRIAL USE ONLY, KEEP OUT REACH FROM CHILDREN.

WASH HANDS BEFORE EATING.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

**ODOR:** Strong ester ketone alcohol

odor COLOR: colored paste

pH: not applicable

**COATING VOC:** 64.8094 **MATERIAL VOC:** 12.8442

### 10. STABILITY AND REACTIVITY

**STABLE:** MATERIAL IS STABLE.

**HAZARDOUS POLYMERIZATION:** Product will not undergo polymerization.

**CONDITIONS TO AVOID:** High temperatures, open flames or sparks.

HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITION MAY YIELD CARBON

DIOXIDE AND/OR CARBON MONOXIDE, ACRID

SMOKE OR METAL FUMES WHEN HEATED TO DECOMPOSITION.

**INCOMPATIBLE MATERIALS:** AVOID MIXING WITH STRONG OXIDIZERS OR REDUCING AGENTS.

# 11. TOXICOLOGICAL INFORMATION

**GENERAL COMMENTS:** None identified.

#### 12. ECOLOGICAL INFORMATION

**ECOTOXICOLOGICAL INFORMATION:** No data available

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** OBEY ALL LOCAL, STATE AND FEDERAL REGULATIONS.

EMPTY CONTAINER: OBEY ALL LOCAL, STATE AND FEDERAL REGULATIONS.

RCRA/EPA WASTE INFORMATION: Obey all local, state and federal regulations.

#### 14. TRANSPORT INFORMATION

# **DOT (DEPARTMENT OF TRANSPORTATION)**

**PROPER SHIPPING NAME:** Flammable Liquid, n.o.s. (acetone)

CLASS: 3 Packing Group: || UN NUMBER: 1993

### 15. REGULATORY INFORMATION

## **UNITED STATES**

SARA TITLE III (SUPERFUND AMENDMENRS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES:

FIRE: X PRESSURE GENERATING: -

**REACTIVITY: - ACUTE:** X CHRONIC: X

**313 REPORTABLE INGREDIENTS:** X


# **302/304 EMERGENCY PLANNING**

**EMERGENCY PLAN:** This product does not contain any extremely hazardous substances.

### **16. OTHER INFORMATION**

# NFPA Rating System

HMIS RATING					
Health:	2				
Flammability:	3				
Reactivity:	0				
Other:	-				



PROTECTIVE EQUIPMENT						
EYES	RESPIRATORY	HANDS	BODY			
	See Section 8		See Section 8			
For Routine Industrial Use and Applications						

MANUFACTURER DISCLAIMER: THE INFORMATION OR RECOMMENDATIONS CONTAINED HEREIN ARE BASED ON INFORMATION OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE AND ARE PROPRIETARY AND ARE FURNISHED SOLELY FOR THE USE OF OUR CUSTOMERS. SINCE IT IS IMPOSSIBLE FOR US TO DETERMINE THE PRECISE CONDITIONS UNDER WHICH OUR PRODUCTS WILL BE USED, NEITHER CLASSIC COATINGS SYSTEMS NOR ITS AFFILIATES CANT ACCEPT RESPONSIBILITY FOR LOSS, INJURY OR OTHER DAMAGES RESULTING FROM THE USE OF THE PRODUCT OR THIS OR ANY OTHER INFORMATION PROVIDED BY US. USERS ARE ADVISED TO MAKE THEIR OWN TESTS TO DETERMINE THE SAFETY, SUITABILITY, AND RELEVANCE OF FEDERAL AND LOCAL LAW TO THE PRODUCT AS IT IS TO BE USED BY THEM. THEREFORE NO GUARANTEE OF ANY KIND EXPRESSED OR IMPLIED, INCLUDING THOSE OF FITNESS OR MERCHANTABILITY, ARE MADE BY CLASSIC COATINGS SYSTEMS OR ITS AFFILIATES WITH REGARD TO ANY OF THEIR PRODUCTS.

**END OF SDS**