

SAFETY DATA SHEET

Issue Date 29-Jun-2021 Revision Date 01-July-2024

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Prime Time - Clear Primer

PRODUCT CODE: PT30

MANUFACTURER

CLASSIC COATINGS SYSTEMS 255 CITATION CIR. CORONA, CA 92878

O:(951) 279-2600

24 HR. EMERGENCY TELEPHONE NUMBER

Emergency Response Service: (800) 535-5053

2. HAZARDS IDENTIFICATION

CLASSIFICATION

GHS Classification:Pictogram:

Signal Word:

Not classified

Not applicable

No signal word

Hazard Statement: No known significant or critical hazards

Prevention: Not applicable
Response: Not applicable
Storage: Not applicable
Disposal: Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number
DIPROPYLENE GLYCOL BUTYL ETHER	0.10	29911-28-2
Ethylene Glycol Monobutyl Ether	0.18	111-76-2
Trade Secret	N/A	***
Trade Secret	N/A	***

4. FIRST AID MEASURES

EYES: Flush with water for 15 minutes. See a physician.

SKIN: Wash skin with soap and water. See a physician if irritation persists.

INGESTION: INGESTION: IF VICTIM IS CONSCIOUS GIVE TWO GLASSES OF WATER AND INDUCE VOMITING. CALL A PHYSCIAN (911) IMMEDIATELY.

INHALATION: INHALATION: REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

5. FIRE FIGHTING MEASURES

FLASH POINT AND METHOD: 149.00 TCC

FLAMMABLE LIMITS: 1.1 TO 10.6

AUTOIGNITION TEMPERATURE: This product will not autoignite.

FLAMMABLE CLASS: Not flammable.

GENERAL HAZARD: MATERIAL WILL NOT SUPPORT COMBUSTION IN THE WET STATE.

EXTINGUISHING MEDIA: Use foam, carbon dioxide or chemical fire fighting apparatus.

FIRE FIGHTING PROCEDURES: The use of self-contained breathing apparatus is recommended for fire fighters. Water spray may be used for cooling containers to prevent possible pressure build-up and autoignition or explosion when exposed to extreme heat. Avoid spreading burning liquid when using water for cooling containers.

FIRE EXPLOSION: CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT OR FLAME DUE TO PRESSURE BUILDUP. COOL CONTAINERS WITH WATER SPRAY.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: DIKE AND CONTAIN SPILLED MATERIAL. ELIMINATE IGNITION SOURCES SUCH AS FLAMES, PILOT LIGHTS, SPARKS AND FLARES. SCOOP UP MATERIAL AND PUT INTO SUITABLE CONTAINER.

LARGE SPILL: OBEY ALL LOCAL, STATE AND FEDERAL REGULATIONS.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: OBEY ALL LOCAL, STATE AND FEDERAL REGULATIONS.

LAND SPILL: OBEY ALL LOCAL, STATE AND FEDERAL REGULATIONS.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: AVOID EXCESSIVE HEAT OR FLAME. DO NOT WELD ON OR NEAR CONTAINER.

KEEP CONTAINERS CLOSED WHEN NOT IN USE.

FOR INDUSTRIAL USE ONLY. KEEP OUT REACH FROM CHILDREN.

WASH HANDS BEFORE EATING.

8. EXPOSURE CONTROLS\PERSONAL PROTECTION

OSHA TABLE COMMENTS:

NL = Not Listed

EXPOSURE LIMITS

Components	CAS	Limits
DIPROPYLENE GLYCOL BUTYL ETHER	29911-28-2	
Ethylene Glycol Monobutyl	111-76-2	PEL: 25 PPM - SKIN
Ether		TLV: 25 PPM - SKIN

ENGINEERING CONTROLS: LOCAL EXHAUST RECOMMENDED.

MECHANICAL EXHAUST RECOMMENDED.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: SAFETY GLASSES OR CHEMICAL SPLASH GOGGLES RECOMMENDED.

SKIN: IMPERMEABLE RUBBER GLOVES RECOMMENDED.

RESPIRATORY: USE NIOSH APPROVED ORGANIC VAPOR RESPIRATOR WHEN PERMISSIBLE

EXPOSURE LIMIT IS EXCEEDED.

WORK HYGIENIC PRACTICES: AVOID EXCESSIVE HEAT OR FLAME. DO NOT WELD ON OR

NEAR CONTAINER.

KEEP CONTAINERS CLOSED WHEN NOT IN USE.

FOR INDUSTRIAL USE ONLY. KEEP OUT REACH FROM CHILDREN.

WASH HANDS BEFORE EATING.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Low odor **COLOR**: Milky **pH**: 8.0-9.0

COATING VOC: <50.0000 **MATERIAL VOC:** 20.0000

10. STABILITY AND REACTIVITY

STABLE: MATERIAL IS STABLE.

HAZARDOUS POLYMERIZATION: Product will not undergo polymerization.

CONDITIONS TO AVOID: High temperatures, open flames or sparks.

HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITION MAY YIELD CARBON DIOXIDE AND/OR CARBON MONOXIDE, ACRID

SMOKE OR METAL FUMES WHEN HEATED TO DECOMPOSITION.

INCOMPATIBLE MATERIALS: AVOID MIXING WITH STRONG OXIDIZERS OR REDUCING AGENTS.

11. TOXICOLOGICAL INFORMATION

GENERAL COMMENTS: None identified.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: No data available,

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: OBEY ALL LOCAL, STATE AND FEDERAL REGULATIONS.

EMPTY CONTAINER: OBEY ALL LOCAL, STATE AND FEDERAL REGULATIONS.

RCRA/EPA WASTE INFORMATION: Obey all local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not regulated TECHNICAL NAME: Paint related material

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENRS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES:

FIRE: - PRESSURE GENERATING: - REACTIVITY: - ACUTE: - CHRONIC: -


313 REPORTABLE INGREDIENTS: -

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: This product does not contain any extremely hazardous substances.

16. OTHER INFORMATION

HMIS RATING		
Health:	1	
Flammability:	0	
Reactivity:	0	
Personal Protection:	В	



MANUFACTURER DISCLAIMER: THE INFORMATION OR RECOMMENDATIONS CONTAINED HEREIN ARE BASED ON INFORMATION OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE AND ARE PROPRIETARY AND ARE FURNISHED SOLELY FOR THE USE OF OUR CUSTOMERS. SINCE IT IS IMPOSSIBLE FOR US TO DETERMINE THE PRECISE CONDITIONS UNDER WHICH OUR PRODUCTS WILL BE USED, NEITHER CLASSIC COATINGS SYSTEMS NOR ITS AFFILIATES CAN ACCEPT RESPONSIBILITY FOR LOSS, INJURY OR OTHER DAMAGES RESULTING FROM THE USE OF THE PRODUCT OR THIS OR ANY OTHER INFORMATION PROVIDED BY US. USERS ARE ADVISED TO MAKE THEIR OWN TESTS TO DETERMINE THE SAFETY, SUITABILITY, AND RELEVANCE OF FEDERAL AND LOCAL LAW TO THE PRODUCT AS IT IS TO BE USED BY THEM. THEREFORE NO GUARANTEE OF ANY KIND EXPRESSED OR IMPLIED, INCLUDING THOSE OF FITNESS OR MERCHANTABILITY, ARE MADE BY CLASSIC COATINGS SYSTEMS OR ITS AFFILIATES WITH REGARD TO ANY OF THEIR PRODUCTS.

END OF SDS