



# ELITE TEXTURE COAT 62

## TECHNICAL DATA SHEET

**6-in-1 All-purpose high-performance cement-based gray overlay for interior and exterior surfaces.**

### DESCRIPTION

Elite Texture Coat 62 is a high-quality, cement-based resurfacing system designed for both horizontal and vertical concrete applications. Engineered with advanced polymer-modified technology, ETC62 delivers strong adhesion, flexibility, and durable performance. It provides contractors with a versatile, easy-to-use product that requires only water to mix—no liquid additives or bond coats necessary.

Ideal for restoring worn concrete, resurfacing pool decks, balconies, and walkways, or applying decorative textures, ETC62 is formulated to reduce surface heat in exposed areas and performs reliably under various climate conditions.

### KEY FEATURES & BENEFITS

- **6-in-1 Versatility** – One mix suitable for broom finish, trowel finish, knockdown texture, stamping, carving, sloped work, stucco, and curbing.
- **Water-Only Mix** – No primer or liquid polymer needed.
- **Strong Bond & Durability** – Excellent adhesion to properly prepared substrates.
- **Interior/Exterior Use** – From pool decks to countertops.
- **Custom Finish Options** – Compatible with integral pigments and topical stains.
- **Sealer-Compatible** – Pairs with Classic Coatings sealers (excluding natural-look sealers).

### INSTALLATION GUIDELINES

#### Surface Preparation

Surfaces must be clean, dry, and free of grease, oil, paint, curing agents, sealer, and other contaminants. Mechanically prepare surfaces via grinding, scarifying, or shot-blasting to achieve a porous profile (CSP 2–3 recommended). Do not acid etch or chemically strip.

#### Mixing

- Use clean potable water.
- Mix 1 full bag with 3.5 quarts of water when Scratch Coat application
- Mix 1 full bag with approximately 1 gallon of water when doing a knock down texture.
- Blend 4–5 minutes using a mechanical mixer until a smooth, lump-free consistency is achieved.
- Do not over water. Use within 15–20 minutes of mixing (70°F).



## Application

Apply between 55°F–85°F surface and ambient temperature. Use appropriate tools such as trowels, hopper guns, squeegees, or brooms depending on desired finish. Maintain uniform thickness and work in small sections to avoid cold joints.

Here's the revised **Coverage Rates** section including the updated **note** about needing two applications with ETC62 for balconies and decorative surfaces:

### Coverage Rates (approx.):

Application Type	Thickness	Coverage (per bag)
Scratch Coat 3.5 quarts	1/16"	150–175 sq. ft.
Broom/Knockdown Finish 1Gal	1/8" (1 coat)	80–110 sq. ft.
Stamped Overlay 3.5 quarts	1/4"	22–25 sq. ft.
Balcony/Decorative Coat 3.5 quarts	1/8" (2 coats)	40–55 sq. ft.

**Note:** When using Elite Texture Coat 62 for balconies or decorative coatings, a **minimum of two applications** is required for best results. Balconies must be waterproofed with Classic's approved system prior to ETC62 application. Coverage may vary depending on surface porosity and profile. Decorative overlays, Microtopping, and porous cementitious surfaces may require an additional coat to achieve the desired appearance and water resistance.

## CURING & FINISHING

- Allow **2 hours between coats** under normal conditions.
- For stain or sealer, after 24 hours after final coat.
- Protect surface from rain, standing water, or moisture prior to sealing.
- Always test sealer compatibility on a small area first.

## LIMITATIONS

- Do not apply below 50°F or above 90°F.
- Not a crack-isolation system. Reflective cracking may occur if the substrate shifts or moves.
- Avoid heavy traffic until fully cured and sealed.
- Not suitable over substrates with active moisture vapor transmission.



## **WORKING TIME & POT LIFE**

- Pot life: ~15–20 minutes at 70°F.
- Working time may vary with temperature, humidity, and wind conditions.

## **PACKAGING & STORAGE**

- 50 lb (22.7 kg) bags
- Store in a cool, dry location. Protect from moisture.
- Shelf life: 12 months unopened.

## **FIRST AID**

### **KEEP AWAY FROM CHILDREN & PETS**

Eyes: Flush with water for 15 minutes

Skin: Wash thoroughly with soap and water

Ingestion: Seek medical attention immediately. Do not induce vomiting

## **CALIFORNIA PROP 65 WARNING**

This product may contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## **WARRANTY / DISCLAIMER**

Classic Coatings Systems warrants this product to be free from manufacturing defects and to conform to published specifications at the time of sale. Liability is limited to replacement of defective material only. No other warranties, express or implied, are made. The user is responsible for determining suitability for the intended use and must perform job-site mock-ups prior to full application.

## **MANUFACTURER**

Classic Coatings Systems  
255 Citation Circle, Corona, CA 92878  
(951) 279-2600  
[www.classiccoatingsystems.com](http://www.classiccoatingsystems.com)  
Revision: 02-17-26