

- 411 Impregnating Seal & Enhance - Water
- 414 Impregnating Natural Sealer - Water
- 416 Impregnating Natural Sealer - Water & Oil
- 418 Impregnating Seal & Enhance - Water & Oil

Date of last alteration: 09/25/2020

1. Product and company identification

1.1 Identification of the substance or preparation:

Commercial product name:

Use of substance / preparation

Industrial

Additive for: Water repellent, building protective agent

1.2 Company/undertaking identification:

Manufacturer/distributor:

Classic Coatings Systems
255 Citation Circle
Corona, CA 92878
USA

Contact information:

Office: (951) 279-2600, Fax: (951) 279-3344

Hours of operation:

Monday - Friday, 8am to 4pm (pacific standard time)

www.classiccoatingsystems.com

Emergency telephone no. (24h):

Emergency Response Service
(800) 535-5053

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (GHS):

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (GHS):

No labeling according to GHS required.



2.3 Other hazards

Inhalation of aerosol spray may damage health.

3. Composition/information on ingredients

3.1 Chemical characterization (preparation)

Chemical characteristics

Polydimethylsiloxane with functional groups (dispersion in water)

3.2 Information on ingredients:

This material does not contain any ingredients above the permitted limit(s).

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in this section are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for non-carcinogenic HAPS or they are inextricably bound in the product. Specific chemical identities and/or exact percentage (concentration) of the composition may have been withheld as a trade secret.

4. First-aid measures

4.1 General information:

Get medical attention if irritation or other symptoms occur. Before seeking medical attention remove contaminated clothing and shoes. Take a copy of the Safety Data Sheet when going for medical treatment.

Safety Data Sheet

Date of last alteration: 09/25/2020

4.2 After inhalation

If inhaled as aerosol, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration.

4.3 After contact with the skin

If contact with skin, immediately flush skin with plenty of water or with water and soap.

4.4 After contact with the eyes

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

4.5 After swallowing

If swallowed, do not induce vomiting. If swallowed, rinse mouth with water. Induce drinking plenty of water in small portions. Get medical attention if symptoms occur. Show label if possible.

5. Fire-fighting measures

5.1 Flammable properties:

Property:	Value:	Method:
Flash point.....	> 93 °C (> 199 °F)	(ASTM D3278, DIN 55680, ISO 3679)
Boiling point / boiling range	not determined	
Lower explosion limit (LEL)	not applicable	
Upper explosion limit (UEL).....	not applicable	
Ignition temperature	not applicable	
NFPA Hazard Class (comb./flam.liquid).....	IIIB	

5.2 Fire and explosion hazards:

This material does not present any unusual fire or explosion hazards.

5.3 Recommended extinguishing media:

Material does not burn. Use extinguishing measures appropriate to the source of fire.

5.4 Unsuitable extinguishing media:

none known .

5.5 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Hazardous decomposition products: carbon dioxide , carbon monoxide , formaldehyde , silicon dioxide and incompletely burnt hydrocarbons .

5.6 Fire fighting procedures:

Fire fighters should wear full protective clothing including a positive pressure self-contained breathing apparatus. Cool endangered containers with water.

6. Accidental release measures

6.1 Precautions:

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. If material is released indicate risk of slipping. Do not walk through spilled material.

HAZWOPER PPE Level: D

6.2 Containment:

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

Safety Data Sheet

Date of last alteration: 09/25/2020

6.3 Methods for cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

7. Handling and storage

7.1 General information:

Always stir well before use.

7.2 Handling

Precautions for safe handling:

Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Spilled substance increases risk of slipping. Observe information in section 8. Keep away from incompatible substances in accordance with section 10.

Precautions against fire and explosion:

Observe the general rules for fire prevention.

7.3 Storage

Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place. Protect against sun. Protect against frost.

Minimum temperature allowed during storage and transportation: 10 °C (50 °F)

Do not allow this material to freeze.

Maximum temperature allowed during storage and transportation: 40 °C (104 °F)

8. Exposure controls and personal protection

8.1 Engineering controls

Ventilation:

Use with adequate ventilation.

Local exhaust:

If spraying or other aerosol generating operations are performed, local exhaust ventilation designed to capture mists and sprays, such as a paint spray booth, is recommended.

8.2 Associate substances with specific control parameters such as limit values

Maximum airborne concentrations at the workplace:

CAS No.	Material	Type	mg/m ³	ppm	Dust fract.
---------	----------	------	-------------------	-----	-------------

none known

8.3 Personal protection equipment (PPE)

Respiratory protection:

Respiratory protection is not normally required. If spraying or other operations which generate an aerosol mist are conducted, respiratory protection for exposed personnel is recommended.

Hand protection:

Recommendation: butyl rubber protective gloves or Any liquid-tight rubber or vinyl gloves.

Eye protection:

Safety glasses with side shields or chemical safety goggles. Where there is risk of splashing: tight fitting chemical safety goggles.

Safety Data Sheet

Date of last alteration: 09/25/2020

Other protective clothing or equipment:

Additional skin protection, such as SARANEX coated Tyvek apron, over-sleeves, lab coat, coveralls, or protective suit should be worn if splashing could occur. Provide eye bath and safety shower.

8.4 General hygiene and protection measures:

Avoid contact with eyes, skin and clothing. Avoid breathing dust/vapor/mist/gas/aerosol. Do not eat or drink when handling. Wash thoroughly after handling.

9. Physical and chemical properties

9.1 Appearance

Physical state / form.....: liquid (25 °C (77 °F))
Colour: milky white to clear
Odour: slight

9.2 Safety parameters

Property:	Value:	Method:
Melting point / melting range	not determined	
Boiling point / boiling range	not determined	
Flash point.....	> 93 °C (> 199 °F)	(ASTM D3278, DIN 55680, ISO 3679)
Ignition temperature	not applicable	
Lower explosion limit (LEL)	not applicable	
Upper explosion limit (UEL).....	not applicable	
Vapour pressure.....	not determined	
Density	1.01 g/cm ³ at 25 °C (77 °F)	
Water solubility / miscibility.....	completely miscible	
pH-Value	9.2	
Viscosity (dynamic)	3.37 mPa.s at 25 °C (77 °F)	

10. Stability and reactivity

10.1 General information:

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

10.2 Conditions to avoid

none known

10.3 Materials to avoid

none known

10.4 Hazardous decomposition products

If stored and handled properly: none known . The following applies for the silicone content of the substance: Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

10.5 Further information:

Hazardous polymerization cannot occur.

11. Toxicological information

11.1 Information on toxicological effects

11.1.1 Acute toxicity

Assessment:

Inhalable aerosols containing aminofunctional polysiloxanes may cause harmful effects in the lung in animal experiments. Due to the large number of influencing parameters (e.g. amine function, degree of substitution, viscosity, composition) an estimation of the toxicological effect on the lung is not possible for untested products of this category. In such cases exposure to inhalable aerosols must be prevented by adequate technical measures.

Safety Data Sheet

Date of last alteration: 09/25/2020

Product details:

Route of exposure	Result/Effect	Species/Test system	Source
oral	LD ₅₀ : > 2000 mg/kg	rat	Conclusion by analogy
dermal	LD ₅₀ : > 2000 mg/kg	rat	Conclusion by analogy

11.1.2 Skin corrosion/irritation

Product details:

Result/Effect	Species/Test system	Source
not irritating	rabbit	Conclusion by analogy

11.1.3 Serious eye damage / eye irritation

Product details:

Result/Effect	Species/Test system	Source
not irritating	rabbit	Conclusion by analogy

11.1.4 Respiratory or skin sensitization

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.5 Germ cell mutagenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.6 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.11 Further toxicological information

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

12. Ecological information

Safety Data Sheet

Date of last alteration: 09/25/2020

12.1 Toxicity

Assessment:

No expected damaging effects to aquatic organisms. According to current knowledge adverse effects on water purification plants are not expected.

Product details:

Result/Effect	Species/Test system	Source
LC ₅₀ : > 100 mg/l	dynamic zebra fish (Danio rerio) (96 h)	Conclusion by analogy
EC ₅₀ : > 1000 mg/l	sludge (3 h)	Conclusion by analogy

12.2 Persistence and degradability

Assessment:

Silicone content: biologically not degradable. Elimination by adsorption to activated sludge. Emulsifier: readily biologically degradable.

12.3 Bioaccumulative potential

Assessment:

Bioaccumulation is not expected to occur.

12.4 Mobility in soil

Assessment:

Separation by sedimentation.

12.5 Other adverse effects

none known

12.6 Additional information

According to our present knowledge no data known.

13. Disposal considerations

13.1 Product disposal

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.2 Packaging disposal

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

14. Transport information

14.1 US DOT & CANADA TDG SURFACE

Valuation: Not regulated for transport

Other Information: Protect from freezing, when exposed to cold temperatures approaching 0 °C (32 °F) or below.

14.2 Transport by sea IMDG-Code

Valuation: Not regulated for transport

14.3 Air transport ICAO-TI/IATA-DGR

Valuation: Not regulated for transport

Safety Data Sheet

Date of last alteration: 09/25/2020

15. Regulatory information

15.1 U.S. Federal regulations

TSCA inventory status and TSCA information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory. This material is in compliance under the 2% Polymer Rule.

TSCA 12(b) Export Notification:

This material does not contain reportable amounts of any TSCA 12(b) listed chemicals.

CERCLA Regulated Chemicals:

This material does not contain any CERCLA regulated chemicals.

SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substances.

SARA 311/312 Hazard Class:

This product does not present any SARA 311/312 hazards.

SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above de minimus levels.

HAPS (Hazardous Air Pollutants):

CAS No.	Chemical	Upper limit wt. %
67-56-1	Methanol	<=0.0153
80-62-6	Methyl methacrylate	<=0.0010

15.2 U.S. State regulations

California Proposition 65 Carcinogens:

This material does not contain any chemicals known to the State of California to cause cancer.

California Proposition 65 Reproductive Toxins:

67-56-1 Methanol

Massachusetts Substance List:

This material contains no listed components.

New Jersey Right-to-Know Hazardous Substance List:

This material contains no listed components.

Pennsylvania Right-to-Know Hazardous Substance List:

This material contains no listed components.

15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

South Korea (Republic of Korea) : **ECL** (Existing Chemicals List):

This product is listed in, or complies with, the substance inventory.

Canada : **DSL** (Domestic Substance List):

This product is listed in, or complies with, the substance inventory.

United States of America (USA)..... : **TSCA** (Toxic Substance Control Act Chemical Substance Inventory):

This product is listed in, or complies with, the substance inventory.

European Economic Area (EEA)..... : **REACH** (Regulation (EC) No 1907/2006):

General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.

16. Other information

16.1 Additional information:

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of

Safety Data Sheet

Date of last alteration: 09/25/2020

the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

16.2 Glossary of Terms:


ACGIH - American Conference of Governmental Industrial Hygienists
DOT - Department of Transportation
hPa - Hectopascals
mPa*s - Milli Pascal-Seconds
OSHA - Occupational Safety and Health Administration
PEL - Permissible Exposure Limit

ppm - Parts per Million
SARA - Superfund Amendments and Reauthorization Act
STEL - Short Term Exposure Limit
TSCA - Toxic Substances Control Act
TWA - Time Weighted Average
WHMIS - Canadian Workplace Hazardous Materials Identification System

Flash point determination methods	Common name
ASTM D56	Tagliabue (Tag) closed cup
ASTM D92, DIN 51376, ISO 2592	Cleveland open cup
ASTM D93, DIN 51758, ISO 2719	Pensky-Martens closed cup
ASTM D3278, DIN 55680, ISO 3679	Setaflash or Rapid closed cup
DIN 51755	Abel-Pensky closed cup

16.3 Conversion table:

Pressure:.....: 1 hPa * 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa
Viscosity:.....: 1 mPa*s = 1 centipoise (cP)



Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet