



# Invisible Shield 2000

## PENETRATING NATURAL LOOK SEALER



### COVERAGE:

1 gallon (3.8 Liters) covers approximately 280 sq. ft. to 400 sq. ft. with two applications

### PACKAGING:

Available in 1 gallon jugs, 5 gallon pails and 55 gallon drums.

### STORAGE:

1. Store in a cool, dry location.
2. Store out of direct sunlight.
3. Protect pails and jugs from weather and other damage.
4. Store at a temperature between 40°F (4°C) and 90°F (32°C).

### SHELF LIFE:

2 years

### COLOR:

Milky  
(Invisible When Dry)

Visit us online:  
[ClassicCoatingSystems.com](http://ClassicCoatingSystems.com)

See Our Website Gallery to Get Inspired and View How-to Videos & SDS

### DESCRIPTION

Classic Coating's Invisible Shield is a clear penetrating sealer & enhancer, single component low VOC, waterborne Sodium Methyl silicate sealer designed to be used over Classic Acid stains, pavers, concrete, stucco, granite, masonry, stone, brick, Spanish tile and some natural stone, provided the surface is properly prepared. It may be used for interior or exterior applications in a wide range of climates. Invisible Shield has excellent UV stability and will not yellow, chalk or peel. It is formulated primarily as a penetrating clear seal for applications over concrete restoration products and pool deck (not slippery) coatings where a low maintenance, easily cleanable surface is desired. It is environmentally safe and cleans with water. **New concrete must cure for 28 days before sealer is apply.**

### ADVANTAGES

Resists water penetration
Waterborne: Low VOC <100g/l, no fumes and low odors
High UV stability & no substrate appearances
Excellent hot tire pick-up
Excellent penetration, durability and abrasion resistance
Low cost, easy installation and low maintenance
Easy to clean with water.

### LIMITATIONS

Not to be used over water based stains
Recommended application temperature should be between 55° F and 100° F
Must be installed over a clean dry surface
Fast drying time about 30 minutes
Not for use under water
Minimum oil penetration

### TYPICAL USAGE

- Pool Decks (not slippery)
- Driveways
- Walkways
- Over acid stained concrete
- Restoration projects
- Architectural toppings
- Concrete floors
- Patios
- Masonry
- Spanish Tile
- Stucco
- Granite
- Travertine Natural Stone

REVISED: March 2017

Classic Coating Systems • 255 Citation, Corona, CA 92880

© 2015 Classic Coatings Systems Inc. All rights reserved.



# Invisible Shield 2000

## PENETRATING NATURAL LOOK SEALER

### PREPARATION

- ✓ **READ SDS BEFORE HANDLING & APPLICATION**
- ✓ Highly recommended to test a small inconspicuous area first.
- ✓ **TURN OFF SPRINKLERS FOR TWO DAYS PRIOR TO AND AFTER.**
- ✓ Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non-masonry surfaces.
- ✓ New concrete must cure for 28 days before sealer is apply.

### INSTALLATION

1. Prepare surface by carefully and thoroughly removing all traces of any foreign matter.
2. Apply first coat of Invisible Shield by a pump sprayer or roller.
3. Repeat step (2) for the second application.
4. Do not leave any excess product to puddle. White residue may appear on surface if not applied correctly. If sealer puddles, use a roller to remove excess.

Cure Time at 77°F: Dry to touch in 30 minutes, re-coat after 1 hour, light foot traffic after 2 hours and full cure in 48 hours.

NOTE: Standard application is two coats.

### PHYSICAL CHARACTERISTICS & TECHNICAL DATA

- Coverage per liquid gallon 280-400 sq. ft. per gallon
- Abrasion - Excellent Resistance
- VOC 89 g/l
- Degree of Gloss – None

It is HIGHLY recommended that on-site samples and mock-ups be made by the applicator. Representative test sections must be produced for the owner's approval in writing and to ensure that applicators are familiar with the product and installation procedures.

Disclaimer: The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind, express or implied is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers and users of this product must comply with all applicable health and safety laws, regulations and orders.

### PRODUCT AVAILABILITY & TECHNICAL ASSISTANCE

Technical assistance and information is available by calling (714) 720-6954  
[www.classiccoatingsystems.com](http://www.classiccoatingsystems.com)

#### HANDLING PRECAUTIONS:

Use only with adequate ventilation. An appropriate cartridge type respirator must be used during application in confined areas. Avoid contact with skin. Protective gloves, eyewear and clothing are recommended.

#### PROP 65 WARNING:

Classic Coatings, as a blender of processed material in the State of California, is required by Proposition 65 to warn that one or more of the components contained in the product contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California (Proposition 65) requires this warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacturing, distribution and intended use. User is solely responsible for the legal disposal of this container and/or its contents.

#### WARRANTY:

Classic Coating products are warranted for one year after date of purchase. Please refer to the Limited Material warranty for additional clarification. NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY. We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE

THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET & FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.