



Multi-Densifier Sealer

A PREMIUM SURFACE DENSITY WATERBASED SEALER



COVERAGE:

1 gallon (3.8 Liters) covers approximately 150sq. ft. to 200 sq.ft.

PACKAGING:

Available in 1 gallon jugs, 5 gallon pails and 55 gallon drums.

STORAGE:

1. Store in a cool, dry location.
2. Store out of direct sunlight.
3. Protect pails and jugs from weather and other damage.
4. Store at a temperature between 40°F (4°C) and 90°F (32°C).

SHELF LIFE:

2 years

COLOR:

Clear low to medium sheen

Visit us online:
ClassicCoatingSystems.com

See Our Website Gallery
 to Get Inspired and
 View How-to Videos & SDS

DESCRIPTION

Classic Multi-Densifier is a low VOC, water based penetrator which is applied to concrete surfaces in order to fill pores and increase surface density. Classic Multi-Densifier can be used on polish and non-polish concrete to reduce dusting and wear. Classic Multi-Densifier has a low to medium sheen and can also be used on driveways, walkways, pool coping and concrete counter tops. Helps with efflorescence and is ideal where a low maintenance, easily cleanable surface is desired. Classic Multi-Densifier is environmentally safe, has excellent penetration and durability, low cost, easy installation and low maintenance. For use indoors and outdoors. Available in 1 gal. jugs, 5 gal. pails and 55 gal. drums. **New concrete must cure for 28 days before stain is applied.**

ADVANTAGES

| |
|---|
| Resists water penetration & waterproof |
| Waterborne: Low VOC <100g/l, no fumes and low odors |
| Cross-Link & High UV stability |
| Excellent hot tire pick-up |
| Excellent penetration and durability |
| Low cost, easy installation and low maintenance |
| Easy to clean with water. |

LIMITATIONS

| |
|---|
| May reflect working cracks in substrate |
| Recommended application temperature should be between 55° F and 95° F |
| Must be installed over a clean dry surface |
| Not freeze thaw |
| Not for use under water |
| Surface must not contain moisture and efflorescence |

TYPICAL USAGE

- Pool Decks
- Driveways
- Walkways
- Over stained concrete
- Restoration projects
- Architectural toppings
- Concrete floors
- Block walls
- Patios
- Masonry
- Spanish Tile
- Stucco
- Natural Stone

REVISED: March 2017

Classic Coating Systems • 255 Citation, Corona, CA 92880

© 2015 Classic Coatings Systems Inc. All rights reserved.



Multi-Densifier Sealer

A PREMIUM SURFACE DENSITY WATERBASED SEALER

PREPARATION

- ✓ **READ SDS BEFORE HANDLING & APPLICATION**
- ✓ Highly recommended to test a small inconspicuous area first.
- ✓ **TURN OFF SPRINKLERS FOR TWO DAYS PRIOR TO AND AFTER.**
- ✓ Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non-masonry surfaces.
- ✓ **Caution:** Surface is slippery when wet.
- ✓ New concrete must cure for 28 days before sealer is apply.

INSTALLATION

1. Prepare surface by carefully and thoroughly removing all traces of any foreign matter.
2. Apply first coat of Classic Multi-Densifier by brush, roller or sprayer.
3. Repeat step (2) for the second coat.
4. A third application may be required in high traffic areas.

Cure Time at 77°F: Dry to touch in 30 minutes, re-coat after 1-2 hours, light foot traffic after 12 hours and full cure in 7 days.

NOTE: System thickness 2-3 wet mils. per coat.
Standard application is two coats.

Classic MEGA DURA, when used with a small percentage of Classic's Series Pigment Concentrate, can also provide a carrier for stain washing and faux finish techniques.

PHYSICAL CHARACTERISTICS & TECHNICAL DATA

- Coverage per liquid gallon 300-450 sq ft per gallon
- Abrasion - Excellent
- VOC 89 g/l
- Degree of Gloss – Hi-Gloss
- Solids content by weight: 29.465%
- Solids content by volume: 29.465 %

It is HIGHLY recommended that on-site samples and mock-ups be made by the applicator. Representative test sections must be produced for the owner's approval in writing and to ensure that applicators are familiar with the product and installation procedures.

Disclaimer: The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind, express or implied is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers and users of this product must comply with all applicable health and safety laws, regulations and orders.

PRODUCT AVAILABILITY & TECHNICAL ASSISTANCE

Technical assistance and information is available by calling (714) 720-6954
www.classiccoatingsystems.com

HANDLING PRECAUTIONS:

Use only with adequate ventilation. An appropriate cartridge type respirator must be used during application in confined areas. Avoid contact with skin. Protective gloves, eyewear and clothing are recommended.

PROP 65 WARNING:

Classic Coatings, as a blender of processed material in the State of California, is required by Proposition 65 to warn that one or more of the components contained in the product contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California (Proposition 65) requires this warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacturing, distribution and intended use. User is solely responsible for the legal disposal of this container and/or its contents.

WARRANTY:

Classic Coating products are warranted for one year after date of purchase. Please refer to the Limited Material warranty for additional clarification. **NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY.** We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. **NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE**

THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET & FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.