



# SAFETY DATA SHEET

Issue Date 3-July-2015

Revision Date 14-June-2017

## 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** PRO-SEAL 2000 HI-GLOSS WET-LOOK – EXEMPT SOLVENT CEMENT SEALER  
**PRODUCT CODE:** CL401

### MANUFACTURER

CLASSIC COATINGS SYSTEMS  
255 CITATION CIR.  
CORONA, CA 92880

24 HR. EMERGENCY TELEPHONE NUMBER  
Hazmat Service: (800) 373-7542

## 2. HAZARDS IDENTIFICATION

### CLASSIFICATION

#### GHS Classification

Flammable Liquid (category 2)  
Serious Eye Irritation (category 2A)  
Specific Target Organ Toxicity, Single Exposure:  
Narcotic Effects (Category 3)



Pictogram:

Signal Word: Danger

Hazard Statements  
H225: Highly flammable liquid and vapor  
H319: Causes serious eye irritation  
H336: May cause drowsiness or dizziness  
H315: Causes skin irritation  
H317: May cause an allergic reaction  
H335: May cause respiratory irritation  
H411: Toxic to aquatic life with long lasting effects

Precautionary Statements: P210: Keep away from heat, sparks, open flame, hot surfaces. No Smoking  
P240: Ground/bond container and receiving equipment  
P241: Use explosion proof electrical/ventilating/lighting equipment  
P242: Use only non-sparking tools  
P243: Take precautionary measure's against static discharge  
P261: Avoid breathing dust/fumes/gas/mist/vapors/spray  
P264: Wash hands thoroughly after handling  
P271: Use only outdoors or in a well ventilated area  
P280: Wear protecting gloves/protecting clothing/eye protection/face protection  
P301+P330+P331+P313: If swallowed: Rinse mouth. Do not induce vomiting. Get medical attention.  
P303+P361+P353: If on skin or hair: Remove all contaminated clothing. Rinse skin with water/shower.  
P304+P340: If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do, Continue rinsing.  
P312: Call a poison center or doctor/physician if you feel unwell.P337+P313: If eye irritation persists: Get medical attention/advice.  
P370+P378: In case of fire: Use dry sand, dry chemical, or alcohol resistant foam for extinction.  
P403+P233+P235+P405: Store in a well ventilated place. Keep container tightly closed. Keep cool. Store locked up.  
P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

## **EMERGENCY OVERVIEW**

**PHYSICAL APPEARANCE :** FLUID COLORED LIQUID WITH SOLVENT ODOR

**IMMEDIATE CONCERNS :** Warning. Flammable liquid and vapor.

## **POTENTIAL HEALTH EFFECTS**

**EYES :** EYES: EXPOSURE TO LIQUID OR VAPORS MAY CAUSE SEVERE EYE IRRITATION. SYMPTOMS MAY INCLUDE BURNING, TEARING, REDNESS, SWELLING, AND EYE DAMAGE.

**SKIN :** May cause skin irritation and sensitization.

**SKIN ABSORPTION :** PROLONGED OR REPEATED EXPOSURE MAY RESULT IN SKIN ABSORPTION OF TOXIC AMOUNTS OF MATERIAL.

**INGESTION :** SWALLOWING MATERIAL CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

**INHALATION :** EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION. CENTRAL NERVOUS SYSTEM EFFECTS INCLUDE DIZZINESS,

WEAKNESS, FATIGUE, NAUSEA, HEADACHE AND POSSIBLE UNCONSCIOUSNESS AND EVEN DEATH.

**CHRONIC** : ASTHMA, BRONCHITIS, EMPHYSEMA, HYPERREACTIVITY, SKIN ALLERGIES, ECZEMA.

**CARCINOGENICITY** : None Known

**MUTAGENICITY** : No known effects.

### REPRODUCTIVE TOXITY

**REPRODUCTIVE EFFECTS** : No known effects.

**TERATOGENIC EFFECTS** : No known effects.

**IRRITANCY**: NO KNOWN ACUTE OR CHRONIC HEALTH HAZARDS.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number
ACETONE	47.90	67-64-1
DIACETONE ALCOHOL	0.45	123-42-2
AROMATIC PETROLEUM DISTILLATE	0.46	64742-94-5
AROMATIC PETROLEUM DISTILLATES	0.15	64742-95-6

\* Toxic chemical subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

### 4. FIRST AID MEASURES

**EYES** : Flush with water for 15 minutes. See a physician.

**SKIN** : Wash skin with soap and water. See a physician if irritation persists.

**INGESTION** : INGESTION: DO NOT INDUCE VOMITING. KEEP PERSON WARM, QUIET, AND GET MEDICAL ATTENTION (911) IMMEDIATELY. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

**INHALATION** : INHALATION: REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

### 5. FIRE FIGHTING MEASURES

**FLASH POINT AND METHOD** : 5.56 °C (42.01 °F) Closed cup

**FLAMMABLE LIMITS** : 1.0 TO 13.39

**AUTOIGNITION TEMPERATURE** : This product will not autoignite.

**FLAMMABLE CLASS :** Flammable liquid category 2

**GENERAL HAZARD :** Danger. Highly flammable liquid and vapor.

**EXTINGUISHING MEDIA :** Use foam, carbon dioxide or chemical fire fighting apparatus.

**FIRE FIGHTING PROCEDURES :** The use of self-contained breathing apparatus is recommended for fire fighters. Water spray may be used for cooling containers to prevent possible pressure build-up and autoignition or explosion when exposed to extreme heat. Avoid spreading burning liquid when using water for cooling containers.

**FIRE EXPLOSION :** CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT OR FLAME DUE TO PRESSURE BUILDUP. COOL CONTAINERS WITH WATER SPRAY. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. DO NOT USE WELDING EQUIPMENT OR CUTTING TORCH ON OR NEAR CONTAINER BECAUSE PRODUCT MAY IGNITE EXPLOSIVELY. THE SAME CAUTIONS APPLY TO EMPTY CONTAINER

## 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL :** DIKE AND CONTAIN SPILLED MATERIAL. ELIMINATE IGNITION SOURCES SUCH AS FLAMES , PILOT LIGHTS, SPARKS AND FLARES. SCOOP UP MATERIAL AND PUT INTO SUITABLE CONTAINER.

**LARGE SPILL :** OBEY ALL LOCAL, STATE AND FEDERAL REGULATIONS.

### ENVIRONMENTAL PRECAUTIONS

**WATER SPILL :** OBEY ALL LOCAL, STATE AND FEDERAL REGULATIONS.

**LAND SPILL :** OBEY ALL LOCAL, STATE AND FEDERAL REGULATIONS.

## 7. HANDLING AND STORAGE

**GENERAL PROCEDURES :** AVOID EXCESSIVE HEAT OR FLAME. DO NOT WELD ON OR NEAR CONTAINER.

KEEP CONTAINERS CLOSED WHEN NOT IN USE.

FOR INDUSTRIAL USE ONLY. KEEP OUT REACH FROM CHILDREN.

WASH HANDS BEFORE EATING.

## 8. EXPOSURE CONTROLS\PERSONAL PROTECTION

### OSHA TABLE COMMENTS:

NL = Not Listed

### EXPOSURE LIMITS

Components	CAS	Limits
ACETONE	67-64-1	PEL: 750 PPM

		TVL: 750 PPM STEL: 1000 PPM
Mixed Esters	MIXTURE	12:00:00 AM
DIACETONE ALCOHOL	123-42-2	
AROMATIC PETROLEUM DISTILLATE	64742-94-5	PEL: 100 PPM TLV: NOT ESTABLISHED
AROMATIC PETROLEUM DISTILLATES	64742-95-6	TLV: NOT ESTABLISHED PEL: 100PPM

**ENGINEERING CONTROLS:** LOCAL EXHAUST RECOMMENDED.  
MECHANICAL EXHAUST RECOMMENDED.

### **PERSONAL PROTECTIVE EQUIPMENT**

**EYES AND FACE:** SAFETY GLASSES OR CHEMICAL SPLASH GOGGLES RECOMMENDED.

**SKIN:** IMPERMEABLE RUBBER GLOVES RECOMMENDED.

**RESPIRATORY:** USE NIOSH APPROVED ORGANIC VAPOR RESPIRATOR WHEN PERMISSIBLE  
EXPOSURE LIMIT IS EXCEEDED.

**WORK HYGIENIC PRACTICES:** AVOID EXCESSIVE HEAT OR FLAME. DO NOT WELD ON OR  
NEAR CONTAINER.

KEEP CONTAINERS CLOSED WHEN NOT IN USE.

FOR INDUSTRIAL USE ONLY. KEEP OUT REACH FROM CHILDREN.

WASH HANDS BEFORE EATING.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

**PHYSICAL STATE :** Liquid

**ODOR :** Stron ester ketone alcohol odor

**COLOR :** colored paste

**pH :** not applicable

**COATING VOC:** 64.8094

**MATERIAL VOC:** 12.8442

## **10. STABILITY AND REACTIVITY**

**STABLE :** MATERIAL IS STABLE.

**HAZARDOUS POLYMERIZATION :** Product will not undergo polymerization.

**CONDITIONS TO AVOID :** High temperatures, open flames or sparks.

**HAZARDOUS DECOMPOSITION PRODUCTS:** THERMAL DECOMPOSITION MAY YIELD CARBON  
DIOXIDE AND/OR CARBON MONOXIDE,ACRID  
SMOKE OR METAL FUMES WHEN HEATED TO DECOMPOSITION.

**INCOMPATIBLE MATERIALS :** AVOID MIXING WITH STRONG OXIDIZERS OR REDUCING AGENTS.

#### 11. TOXICOLOGICAL INFORMATION

**GENERAL COMMENTS:** None identified.

#### 12. ECOLOGICAL INFORMATION

**ECOTOXICOLOGICAL INFORMATION:** No data available,

#### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** OBEY ALL LOCAL, STATE AND FEDERAL REGULATIONS.

**EMPTY CONTAINER:** OBEY ALL LOCAL, STATE AND FEDERAL REGULATIONS.

**RCRA/EPA WASTE INFORMATION:** Obey all local, state and federal regulations.

#### 14. TRANSPORT INFORMATION

**DOT (DEPARTMENT OF TRANSPORTATION)**

**PROPER SHIPPING NAME :** Flammable liquid density > 20 - Paint related material.

**CLASS:** 3

**Packing Group:** II

**UN NUMBER:** 1263

#### 15. REGULATORY INFORMATION

##### UNITED STATES

##### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

##### 311/312 HAZARD CATEGORIES:

**FIRE :** X                      **PRESSURE GENERATING :** -

**REACTIVITY :** -    **ACUTE :** X    **CHRONIC :** X

**313 REPORTABLE INGREDIENTS:** X


##### 302/304 EMERGENCY PLANNING

**EMERGENCY PLAN:** This product does not contain any extremely hazardous substances.

## 16. OTHER INFORMATION

HMIS RATING	
Health :	2
Flammability:	3
Reactivity:	0
Personal Protection:	G

### NFPA CODES



**MANUFACTURER DISCLAIMER :** THE INFORMATION OR RECOMMENDATIONS CONTAINED HEREIN ARE BASED ON INFORMATION OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE AND ARE PROPRIETARY AND ARE FURNISHED SOLELY FOR THE USE OF OUR CUSTOMERS. SINCE IT IS IMPOSSIBLE FOR US TO DETERMINE THE PRECISE CONDITIONS UNDER WHICH OUR PRODUCTS WILL BE USED, NEITHER CLASSIC COATINGS SYSTEMS NOR ITS AFFILIATES CAN ACCEPT RESPONSIBILITY FOR LOSS, INJURY OR OTHER DAMAGES RESULTING FROM THE USE OF THE PRODUCT OR THIS OR ANY OTHER INFORMATION PROVIDED BY US. USERS ARE ADVISED TO MAKE THEIR OWN TESTS TO DETERMINE THE SAFETY, SUITABILITY, AND RELEVANCE OF FEDERAL AND LOCAL LAW TO THE PRODUCT AS IT IS TO BE USED BY THEM. THEREFORE NO GUARANTEE OF ANY KIND EXPRESSED OR IMPLIED, INCLUDING THOSE OF FITNESS OR MERCHANTABILITY, ARE MADE BY CLASSIC COATINGS SYSTEMS OR ITS AFFILIATES WITH REGARD TO ANY OF THEIR PRODUCTS

END OF SDS