



Classic Stripper

AN ENVIRONMENTALLY FRIENDLY PAINT & SEALER STRIPPER



COVERAGE:

1 gallon (3.8 Liters) covers approximately 300 - 350 sq. ft.

Note: do not dilute.

PACKAGING:

Available in 1 gallon jugs, 5 gallon pails and 55 gallon drums.

STORAGE:

1. Store in a cool, dry location.
2. Store out of direct sunlight.
3. Protect pails and jugs from weather and other damage.
4. Store at a temperature between 40°F (4°C) and 90°F (32°C).

SHELF LIFE:

3 years
Unopened in its original container

Visit us online:
ClassicCoatingsSystems.com

See Our Website Gallery
to Get Inspired and
View How-to Videos & SDS

DESCRIPTION

Classic Stripper is biodegradable, non-flammable, VOC compliant in all 50 states and is an environmentally friendly coating remover. The product does not contain any methylene chloride, caustics or toxic chemicals. It does not contain any carcinogens or deplete the ozone like some competitive products. Classic Stripper is highly effective in removing the most durable industrial coatings. It can be used to remove tough acrylics, paints, lacquer sealer, latex paints, alkyd paints and oil-based enamels on all types of substrates including concrete, masonry, brick, wood, steel, aluminum and metal alloys. Classic Stripper is not harmful like methylene chloride based strippers, it is not sticky or messy like soy based strippers and offers cost savings over labor intensive mechanical stripping methods.

ADVANTAGES

Environmentally Friendly
Does not contain caustics or toxic chemicals
Cost savings over mechanical stripping
Can be used for interior and exterior
Zero VOC Compliant in all 50 states
Non-Flammable
Non-hazardous shipping

LIMITATIONS

Harmful to vinyl tile, linoleum, synthetics & PVC pipes
Do not use on asphalt, plastics or rubber

TYPICAL USAGE

Classic Stripper is safe for both indoor and outdoor use which includes the following but not limited to:

- Concrete & Masonry
- Acrylics
- Paint & Latex
- Tile Sealers
- Stains
- Lacquers



Classic Stripper

AN ENVIRONMENTALLY FRIENDLY PAINT & SEALER STRIPPER

SURFACE PREPARATION

- ✓ **READ SDS BEFORE HANDLING & APPLICATION**
- ✓ Highly recommended to test a small inconspicuous area first.
- ✓ Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non-masonry surfaces.
- ✓ Caution: Surface is slippery when wet.
- ✓ Before you start, be sure to wear rubber gloves & safety glasses

APPLICATION

Classic Stripper is a ready to use product that's easy to apply using a roller or brush. The product should be applied at twice the thickness of the coating that is being removed. It must not dry out during the stripping process so it is recommended that it is covered with a plastic sheet. The coating is normally stripped in 4-6 minutes but it can be significantly longer for coatings with multiple layers. After stripping the coating can be removed using a scraper, dry rag, steel wool, ShopVac or Power Wash. Some floors may require you to apply two applications. Wash with a minimum 3,100 psi pressure washer. Coverage rate will vary depending on the substrate and coating thickness. Use caution when walking on the floor as it will be slippery. Allow the surface to dry before applying a sealer or finish.

LIMITATIONS

Classic Stripper is harmful to vinyl tile, linoleum, asphalt, plastics, rubber and synthetics. This product will remove old adhesive residue from tile, carpet and wood flooring. Classic Coatings Systems liability, either expressed or implied is limited solely to the replacement of this product, when proven to be defective and does not include any labor cost or consequential damages.

MATERIAL HANDLING

Refer to our website for our Safety Data Sheets. Please review Classic Coatings Technical application specification for full installation procedures, however prior to use or handling material, thoroughly read all safety precautions and safety data sheets (SDS). www.ClassicCoatingsSystems.com

CAUTION

Keep away from children. Do not take internally. Contact may cause eye or skin irritation. Always use safety gloves, appropriate eye protection and appropriate OSHA/ NOSH approved respirator in areas with poor ventilation, and when exposed to spray mist, both outdoors and indoors. Refer to SDS for handling instructions. **FIRST AID:** If ingested, seek medical attention immediately, in case of eye contact, wash thoroughly with soap and water, if irritation occurs, seek medical attention.

KEEP OUT OF REACH OF CHILDREN & PETS

DISCLAIMER

Classic Coatings believes this information to be true to the best of our knowledge and products are of the highest quality and uniform within manufacturing tolerances. Since no control is exercised over product use, no warranty, expressed or implied is made to the effect of such use and no liability is assumed directly or indirectly from their use. Buyers and users are encouraged to conduct their own test prior to application.

HANDLING PRECAUTIONS:

Use only with adequate ventilation. An appropriate cartridge type respirator must be used during application in confined areas. Avoid contact with skin. Protective gloves, eyewear and clothing are recommended.

PROP 65 WARNING:

Classic Coatings, as a blender of processed material in the State of California, is required by Proposition 65 to warn that one or more of the components contained in the product contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California (Proposition 65) requires this warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacturing, distribution and intended use. User is solely responsible for the legal disposal of this container and/or its contents.

WARRANTY:

Classic Coating products are warranted for one year after date of purchase. Please refer to the Limited Material warranty for additional clarification. **NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY.** We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. **NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE**

THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may CAUSE SERIOUS PHYSICAL INJURY. **BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET & FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.**

Technical assistance and info. is available by calling: (714) 720-6954
www.ClassicCoatingsSystems.com