



# Super Eco-Etch

## AN ORGANIC ACID REPLACEMENT CLEANER – ZERO VOC



### COVERAGE:

1 gallon (3.8 Liters) covers approximately 250sq. ft. to 400 sq.ft.

### PACKAGING:

Available in 1 gallon jugs, 5 gallon pails and 55 gallon drums.

### STORAGE:

1. Store in a cool, dry location.
2. Store out of direct sunlight.
3. Protect pails and jugs from weather and other damage.
4. Store at a temperature between 40°F (4°C) and 90°F (32°C).

### SHELF LIFE:

3 years

### COLOR:

Clear

Visit us online:  
[ClassicCoatingSystems.com](http://ClassicCoatingSystems.com)

See Our Website Gallery  
 to Get Inspired and  
 View How-to Videos & SDS

### DESCRIPTION

**C** Classic Super Eco-Etch is an Organic Acid replacement technology with Zero VOC, a low ph salt that is used to replace traditional acid. There is no need for neutralizing. 4 to 10 times more effective than citric and glycolic acid and 4 to 5 more effective than phosphoric acid when dissolving calcium carbonate, classified as a mild skin irritant and non-corrosive to skin, mild steel & no fumes, approved by the US EPA as a non-food inert ingredient in bio-degradable applications. For use on pool decks, concrete slabs, stone, brick and grout joints. It may be used for interior or exterior applications in a high traffic areas in a wide range of climates. Excellent cleaner and etcher. Environmentally safe and cleans up with water. **New concrete must cure for 28 days.**

### ADVANTAGES

Non- Hazards and Non-Corrosive
Waterborne – Zero VOC
Non-Corrosive to skin and mild steel
Bio-Degradable & Environmentally safe
Safe to use around lawn and plants
Etch concrete and rinse well
No need for sandblasting
Removes grout haze cement residue, grease, oil and efflorescence.
Leaves a sandblasted finish look

### LIMITATIONS

Keep container close at all time when not in use
Applications temperature should be between 45° F and 100° F
Must rinse well with water
Not freeze thaw

\* Highly recommended to do a sample first.

### TYPICAL USAGE

- Pool Decks
- Driveways
- Garage Floors
- Work Shops
- Restoration projects
- Concrete floors
- Bricks
- Stone
- New and old concrete side walks



# Super Eco-Etch

AN ORGANIC ACID REPLACEMENT CLEANER \_ ZERO VOC

## PREPARATION

- ✓ **READ SDS BEFORE HANDLING & APPLICATION**
- ✓ Highly recommended to test a small inconspicuous area first.
- ✓ **TURN OFF SPRINKLERS FOR TWO DAYS PRIOR TO AND AFTER.**
- ✓ Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non-masonry surfaces.
- ✓ **Caution: Surface is slippery when wet.**
- ✓ New concrete must cure for 28 days before sealer is apply.

## INSTALLATION

1. Prepare surface by careful and thorough removal of laitance, grease and foreign matter.
2. Apply first coat with a saturated brush , mop or a low pressure garden type sprayer.
3. Power wash with 2,700 psi and rinse well with water.

**NOTE:** It is **HIGHLY** recommended that on-site samples and mock-ups be made by the applicator. Representative test sections must be produced for the Owner's approval in writing and to ensure applicators are familiar with the product and installation procedures.

## PHYSICAL CHARACTERISTICS & TECHNICAL DATA

It is **HIGHLY** recommended that on-site samples and mock-ups be made by the applicator. Representative test sections must be produced for the owner's approval in writing and to ensure that applicators are familiar with the product and installation procedures.

**Disclaimer:** The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind, express or implied is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers and users of this product must comply with all applicable health and safety laws, regulations and orders.

## PRODUCT AVAILABILITY & TECHNICAL ASSISTANCE

Technical assistance and information is available by calling (714) 720-6954  
[www.classiccoatingsystems.com](http://www.classiccoatingsystems.com)

### HANDLING PRECAUTIONS:

Use only with adequate ventilation. An appropriate cartridge type respirator must be used during application in confined areas. Avoid contact with skin. Protective gloves, eyewear and clothing are recommended.

### PROP 65 WARNING:

Classic Coatings, as a blender of processed material in the State of California, is required by Proposition 65 to warn that one or more of the components contained in the product contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California (Proposition 65) requires this warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacturing, distribution and intended use. User is solely responsible for the legal disposal of this container and/or its contents.

### WARRANTY:

Classic Coating products are warranted for one year after date of purchase. Please refer to the Limited Material warranty for additional clarification. **NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY.** We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. **NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE**

**THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT.** We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET & FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.